

mark I

High Performance and Low Cost in One Complete Package!

The **MARK I** incorporates industry-leading technology, pricing, and service to be the leader in travel document delivery systems. Powered by an internal PC, the **MARK I** is the clear choice for travel agencies, airports, and satellite ticket printing applications.

Features of the **MARK I** include:

- ▶ Print speeds up to 40 documents per minute
- ▶ Standard front feed revalidation
- ▶ Three autoloading ticket bins (two locked)
- ▶ Internal PC system
- ▶ Three open PC slots for expansion



S P E C I F I C A T I O N S

Print Technology

- Direct Thermal
- 203dpi (8dpmm) print resolution
- Full graphics capability
- Optional Character Fonts
- Processes up to 40 documents per minute

Documents

- Issues ATB1 or ATB2 coupons
- Three auto-loading input bins
- Fan-folded, continuous feed stock with burst separation from three separate bins
- Accepts 8" and 7 3/8" stock lengths
- Front feed revalidation path
- Internal void bin

Magnetics, Optional

- Encoding to IATA RP 1722 and Resolution 722
- Fully ATB2 compliant
- Four tracks - read, write, and write verification (210 bpi)
- SCN pre-read prior to bursting

Communications Interface

- Dual RS232 serial ports
- Optional integrated LAN interface
- Supports all popular ATB interfaces including AEA specifications

Physical Characteristics

- Width = 11 5/8 inches (295 mm)
- Height = 23 1/2 inches (597 mm)
- Depth = 21 3/4 inches (552 mm)
- Weight = 67 pounds (28 kg)

Power

- 115 / 220 VAC (+/- 10%) auto-sensing
- 50/60 Hz

Environment

- Operating Temperature 40F to 104F (4C to 40C)
- Storage Temperature -4F to 140F (-20C to 60C)
- FCC, UL, CE, CSA, and TUV

Compliance

- Fully compliant with IATA ATB2 specifications
- Compliant with ATA Resolutions
- FCC, UL, CE, CSA, and TUV

Options

- Magnetic encoding module
- Integrated LAN interface
- Hard Disk Drive
- Large Capacity Stacker
- Internal Modem

Specifications Subject to Change